Stroud Systems, Inc.

713-861-3270

sales@stroudsystems.com



Mi-Glow[®] 600LS-RTU

Physical Characteristics

Red liquid, odorless.

Particle Certification

Particles, carrier and mixture meet or exceed all relevant industry specifications. Certification is included with each shipment.

Particle Color Red

Average Particle Size 10 µm

AMS Standard Not applicable.

SAE Sensitivity Not applicable.

Temperature Range 32-120°F (0-49°C)

Related Product Information:

Material Safety Data Sheet Technical Bulletin 275

Item # FG-2890 Package Size 6 quarts/case

Stroud Systems, Inc. 600 North Shepherd Drive, Suite 115 Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com



www.circlesafe.com P.O. Box 1228, Hinckley, Illinois 60520 ph 815.286.3271 | fax 815.286.3352 email customerservice@circlesafe.com

Circle Systems, Inc.

to-Use oil bath packaged in a hand-held spray bottle. The bath contains Mi-Glow[®] 600 red particles and CircleSol M[™], a refined petroleum distillate. It is designed to be used with visible light for revealing discontinuities found in structural fabrications. Mi-Glow[®] 600LS-RTU can be further enhanced when used

with a UV-A light or blue light.

Mi-Glow[®] 600LS-RTU is a Ready-

MI-GLOW 600LS-RT