



Mi-Glow®

Mi-Glow® 800LS-RTU

Physical Characteristics

Forest green liquid, odorless.

Particle Certification

Particles, carrier and mixture meet or exceed all relevant industry specifications, including but not limited to ASTM E-1444, MIL-STD-271, ASTM E 709, ASME B & PV Code - Section V and NAVSEA 250-1500-1, AMS 3045, AMS 3161, AMS 2641 and A-A-59230. Certification is included with each shipment.

Particle Color

Flourescent yellow-green

Average Particle Size

5 µm

AMS Standard

3045

SAE Sensitivity*

8

[*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

Temperature Range

32-120°F (0-49°C)

Related Product Information:

Material Safety Data Sheet

Technical Bulletin 277

Item

FG-3145

Package Size

6 quarts/case

Stroud Systems, Inc.
600 North Shepherd Drive, Suite 115
Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com



Mi-Glow® 800LS-RTU is a Ready-to-Use oil bath packaged in a hand-held spray bottle. The bath contains Mi-Glow® 800 fluorescent yellow-green particles and CircleSol M™, a refined petroleum distillate. It is designed for revealing very fine discontinuities, such as those found in finished products for the aerospace industry and other critical applications, using UV-A light.



Circle Systems, Inc.

www.circlesafe.com

P.O. Box 1228, Hinckley, Illinois 60520

ph 815.286.3271 | fax 815.286.3352

email customerservice@circlesafe.com