



# Mi-Glow<sup>®</sup>

## Mi-Glow<sup>®</sup> 820LS-RTU

### Physical Characteristics

Black liquid, odorless.

### Particle Certification

Particles, carrier and mixture meet or exceed all relevant industry specifications, including but not limited to ASTM E-1444, MIL-STD-271, ASTM E 709, ASME B & PV Code - Section V and NAVSEA 250-1500-1, AMS 3041, AMS 3042, AMS 2641 and A-A-59230. Certification is included with each shipment.

### Particle Color

Black

### Average Particle Size

1.5  $\mu$ m

### AMS Standard

3041

### SAE Sensitivity\*

6

[\*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

### Temperature Range

32-120°F (0-49°C)

### Related Product Information:

Material Safety Data Sheet

Technical Bulletin 278

### Item #

FG-3622

### Package Size

6 quarts/case

Stroud Systems, Inc.  
600 North Shepherd Drive, Suite 115  
Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com



Mi-Glow<sup>®</sup> 820LS-RTU is a Ready-to-Use oil bath packaged in a hand-held spray bottle. The bath contains Mi-Glow<sup>®</sup> 106 black particles and CircleSol M<sup>™</sup>, a refined petroleum distillate. It is designed to be used with visible light for revealing discontinuities on machined component parts.



## Circle Systems, Inc.

www.circlesafe.com

P.O. Box 1228, Hinckley, Illinois 60520

ph 815.286.3271 | fax 815.286.3352

email customerservice@circlesafe.com