



Mi-Glow®

Mi-Glow® 820S-RTU

Physical Characteristics

Black solution with a slight detergent odor.

Particle Certification

Particles meet or exceed all relevant industry specifications, including but not limited to ASTM E 1444, AMS 3042, MIL-STD-271, NAVSEA 250-1500-1, NTR-1E. Certification is included with each shipment.

Particle Color

Black

Average Particle Size

1.5 μm

AMS Standard

3042

SAE Sensitivity*

6

[*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

Temperature Range

32-120°F (0-49°C)

Related Product Information:

Material Safety Data Sheet

Technical Bulletin 279

Item

FG-3612

Package Size

6 quarts/case



Mi-Glow® 820S-RTU is a Ready-to-Use water bath packaged in a hand-held spray bottle.

The water bath contains Mi-Glow® 106 black particles and liquid Wetting Agent 771. It is designed to be used with visible light for revealing discontinuities on machined component parts.

Stroud Systems, Inc.
600 North Shepherd Drive, Suite 115
Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com



Circle Systems, Inc.

www.circlesafe.com

P.O. Box 1228, Hinckley, Illinois 60520

ph 815.286.3271 | fax 815.286.3352

email customerservice@circlesafe.com