



Physical Characteristics

Black solution with a slight detergent odor.

Particle Certification

Particles meet or exceed all relevant industry specifications, including but not limited to ASTM E 1444, AMS 3042, MIL-STD-271, NAVSEA 250-1500-1, NTR-1E. Certification is included with each shipment.

Particle Color

Black

Average Particle Size

1.5 µm

AMS Standard

3042

SAE Sensitivity*

6

[*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

Temperature Range

32-120°F (0-49°C)

Related Product Information:

Material Safety Data Sheet Technical Bulletin 265

Item

Package Size

FG-3611

Case of 4 - 1 Quart Bottles

Stroud Systems, Inc. 600 North Shepherd Drive, Suite 115 Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com

Circle Systems, Inc.

www.circlesafe.com

P.O. Box 1228, Hinckley, Illinois 60520 ph 815.286.3271 | fax 815.286.3352 email customerservice@circlesafe.com



Mi-Glow[®] 106 black particles

premixed with liquid Wetting

Agent 771 for use in water

media. Higher particle

concentration provides heavier indication buildup for easy

detection. It is designed to be used with visible light for

finding discontinuities in finished

products. Mi-Glow® 820 can be

used with Mi-Glow® WCP.