



# CircleSafe®



## CircleSafe® 850AX

### Physical Characteristics

Red liquid, slight odor contained in an aerosol package.

### Particle Certification

Particles, carrier and mixture meet or exceed all relevant industry specifications. Certification is included with each shipment.

### Particle Color

Red

### Average Particle Size

10 µm

### AMS Standard

Not applicable.

### SAE Sensitivity

Not applicable.

### Temperature Limit

120°F Maximum

### Related Product Information:

Material Safety Data Sheet  
Technical Bulletin 281

### Item #

FG-3636

### Package Size

Case of 12 x 16 oz. Cans

CircleSafe® 850AX is an aerosol spray can of Mi-Glow® 600 red particles and CircleSol M™, a refined petroleum distillate. It is designed to be used with visible light inspection for detecting discontinuities found in structural fabrications and weldments. Higher particle concentration provides heavier indication buildup for easy detection. CircleSafe® 850AX can be further enhanced when used with UV-A light or blue light. The carbon dioxide propellant reduces combustible hazard.

**Stroud Systems, Inc.**  
600 North Shepherd Drive, Suite 115  
Houston, TX 77007-1324

**713-861-3270**

**sales@stroudsystems.com**



**Circle Systems, Inc.**

**www.circlesafe.com**

P.O. Box 1228, Hinckley, Illinois 60520

ph 815.286.3271 | fax 815.286.3352

email customerservice@circlesafe.com