
Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: SKC-S
Product Code: Not available.

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Non-Destructive Testing.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Magnaflux
155 Harlem Avenue,
Glenview, Illinois
60025

Telephone Number: 847-657-5300

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: CHEMTREC 800-424-9300
Date of Preparation: November 25, 2013 **Version #:** 1.1

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012**Hazard class**

Flammable Liquid 2
Aspiration hazard 1

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012**Hazard Pictogram:**

Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor. May be fatal if swallowed and enters airways.

Prevention: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response: In case of fire: Use foam, carbon dioxide to extinguish. Never use

water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage:
Disposal:


Store in a well-ventilated place. Keep cool. Store locked up.
Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

- Class B2 - Flammable Liquid
- Class D2A - Teratogenicity and Embryotoxicity
- Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



WHMIS Signal Word: WARNING

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	UN #	H / F / R / *	CAS No	Wt. %
Naphtha (petroleum), hydrotreated light	Not available	Not available	64742-49-0	60 - 100
Xylene	UN1307	2/3/0	1330-20-7	0.5 - 1.5
Ethylbenzene	UN1175	2/3/0	100-41-4	< 0.1
Toluene	UN1294	2/3/0	108-88-3	< 0.1
Benzene	UN1114	2/3/0	71-43-2	< 0.1
Naphthalene	UN1334 / UN2304	2/2/0	91-20-3	< 0.1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

- Eye:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, including under lids. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin:** In case of contact, immediately flush skin with plenty of water. Do not use ointments. Call a physician if irritation develops and persists.
- Inhalation:** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

- Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.
- Ingestion:** May be fatal if swallowed and enters airways. May cause stomach distress, nausea or vomiting. This product may be aspirated into the lungs and cause chemical pneumonitis.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

- Note to Physicians:** Symptoms may not appear immediately.
- Specific Treatments:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

- Flammability:** Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

5.2 EXTINGUISHING MEDIA

- Suitable Extinguishing Media:** Foam, carbon dioxide.

Unsuitable Extinguishing Media: Water.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Avoid water in straight hose stream; will scatter and spread fire. Spills of this material are a slipping hazard.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Scoop up material and place in a disposal container. Provide ventilation.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Keep away from heat/sparks/open flames/hot surfaces.- No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist /vapors/spray. Do not swallow. Handle and open container with care. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. Use only non-sparking tools. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed. Store in a cool, well ventilated area. Keep away from sources of ignition. Store locked up. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits		
Ingredient	OSHA-PEL	ACGIH-TLV
Naphtha (petroleum), hydrotreated light	Not available.	Not available.
Xylene	100 ppm	100 ppm
Ethylbenzene	100 ppm	20 ppm
Toluene	200 ppm	20 ppm
Benzene	10 ppm	0.5 ppm
Naphthalene	10 ppm	10 ppm

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

Skin Protection:

Hand Protection: Chemical-resistant gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

General Health and Safety Measures: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Colorless.
Odor:	Naphtha odor.
Odor Threshold:	Not available.
Physical State:	Liquid.
pH:	Neutral.
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	~ 118 °C (~ 245 °F)
Flash Point:	~ 14 °C (~ 57 °F)
Evaporation Rate:	Fast.
Flammability:	Flammable.

Lower Flammability/Explosive Limit:	1%
Upper Flammability/Explosive Limit:	6%
Vapor Pressure:	1.5 – 2.0 kPa @ 20°C (68 °F)
Vapor Density:	4.1
Relative Density/Specific Gravity:	0.76
Solubility:	Insoluble.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	0.786 cSt
Oxidizing Properties:	Not available.
Explosive Properties:	Not available.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Heat. Incompatible materials. Sources of ignition.

10.5 INCOMPATIBLE MATERIALS

Strong oxidizing agents.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon and organic compounds.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Ingestion: May be fatal if swallowed and enters airways. May cause stomach distress, nausea or vomiting. This product may be aspirated into the lungs and cause chemical pneumonitis.

Inhalation: May cause respiratory tract irritation. May cause drowsiness or dizziness.

Acute Toxicity:

Ingredient	IDLH	LC50	LD50
Naphtha (petroleum), hydrotreated light	Not available.	Not available.	Oral >5000 mg/kg, rat Dermal >3160 mg/kg, rabbit
Xylene	900 ppm	Inhalation 5000 ppm 4 h, rat	Oral 4300 mg/kg, rat Dermal >1700 mg/kg, rabbit
Ethylbenzene	800 ppm	Inhalation 17.2 mg/L 4h, rat	Oral 3500 mg/kg, rat Dermal 15354 mg/kg, rabbit
Toluene	500 ppm	Inhalation 28.1 mg/L 4h, rat	Oral >5000 mg/kg, rat Dermal 8390 mg/kg, rabbit Dermal 12124 mg/kg, rat
Benzene	500 ppm	Inhalation 13050-14380 ppm 4h, rat	Oral 930 mg/kg, rat Dermal > 9.4mL/kg, rabbit
Naphthalene	250 ppm	Inhalation >0.4 mg/L 4 h, rat	Oral 490 mg/kg, rat Dermal >2500 mg/kg, rat Dermal >20 g/kg, rabbit

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
Not available.	> 2000 mg/kg, rat	> 2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Naphtha (petroleum), hydrotreated light	Not listed.
Xylene	G-A4, I-3
Ethylbenzene	G-A3, I-2B, CP65
Toluene	G-A4, I-3, CP65
Benzene	O, G-A1, I-1, N-1, CP65
Naphthalene	G-A4, I-2B, N-2, CP65

* See Section 15 for more information.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

- Skin Corrosion/Irritation:** May cause skin irritation.
- Serious Eye Damage/Irritation:** May cause eye irritation.
- Respiratory Sensitization:** Based on available data, the classification criteria are not met.
- Skin Sensitization:** Based on available data, the classification criteria are not met.
- STOT-Single Exposure:** Based on available data, the classification criteria are not met.
- Chronic Health Effects:**

Carcinogenicity: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met.

Teratogenicity: Hazardous by WHMIS criteria.

Embryotoxicity: Hazardous by WHMIS criteria.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Based on available data, the classification criteria are not met.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Toxicologically Synergistic Materials: Not available.

Other Information: Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Floats on water.

Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

Section 14: TRANSPORT INFORMATION

DOT	UN 1268, Petroleum distillates, n.o.s., 3, II
IATA	UN 1268, Petroleum distillates, n.o.s., 3, II (cargo aircraft only)
IMDG	UN 1268, Petroleum distillates, n.o.s., 3, II (Non-bulk only)

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Naphtha (petroleum), hydrotreated light	Not listed.	Not listed.	Not listed.	Not listed.
Xylene	Not listed.	Not listed.	100	313
Ethylbenzene	Not listed.	Not listed.	1,000	313
Toluene	Not listed.	Not listed.	1,000	313
Benzene	Not listed.	Not listed.	10	313
Naphthalene	Not listed.	Not listed.	100	313

State Regulations

California Proposition 65:

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories:

Ingredient	Canada DSL/NDSL	USA TSCA
Naphtha (petroleum), hydrotreated light	DSL	Yes.
Xylene	DSL	Yes.
Ethylbenzene	DSL	Yes.
Toluene	DSL	Yes.
Benzene	DSL	Yes.
Naphthalene	DSL	Yes.

NFPA-National Fire Protection Association:

Health:	1
Fire:	3
Reactivity:	0

HMIS-Hazardous Materials Identification System:

Health:	1*
Fire:	3
Physical Hazard:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:**CP65** **California Proposition 65****OSHA (O)** **Occupational Safety and Health Administration.****ACGIH (G)** **American Conference of Governmental Industrial Hygienists.**

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) **International Agency for Research on Cancer.**

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) **National Toxicology Program.**

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: November 25, 2013**Expiry Date:** November 25, 2016**Version:** 1.1**Revision Date:** June 9, 2015**Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards**

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com

Prepared for: Magnaflux

End of Safety Data Sheet