

## SPOTCHECK<sup>®</sup> SKC-S

### GENERAL DESCRIPTION

SKC-S is used as a cleaner / remover in the penetrant inspection process.

### COMPOSITION

SKC-S contains petroleum naphtha and is non-halogenated.

### TYPICAL PROPERTIES (Not a specification)

Typical Properties	SKC-S
Color	Clear, Colorless
Odor	Very Low Odor
Flash Point	57°F (PMCC)
Density	6.26 lbs./gal
Vapor Pressure	30 mm Hg @68°F
Corrosion	Meets AMS-2644 Requirements
Non Volatile Residue	<50 ppm
VOC	750 g/l
NPE-Free	Yes

### METHOD OF APPLICATION

Apply product to a cloth, wipe test surface and repeat as needed.

**Warning!** Do not spray SKC-S directly on the part because penetrant indications may be removed.

**SPECIFICATION COMPLIANCE:** AMS-2644, MIL-STD-271, MIL-STD-2132; AECL, ASTM E 165, ASTM E 1417, ASME B&PV Code, Section V, NAVSEA 250-1500-1, Boeing PS-21202, ISO 3452-2

### PACKAGING

1 Gal. Cans (case of 4), 5 Gal. Pail, 55 Gal. Drum, Aerosols.

### COVERAGE

(1) Gal. covers approximately 800 square feet.

(1) 16 fl. oz. aerosol can covers approximately 65 square feet.