


NDT Inspection Plugs

Petroleum Refining · Chemical · Petrochemical · Paper and Pulp · Power Generation · Air Handling · Manufacturing · Transportation

Easy, Resealable Access for
Nondestructive Testing of
Insulated Pipe and Equipment

Install Once.
Inspect As Often
As You Choose!



- EPA and OSHA inspection point access
- Reduces time for periodic inspections/tests
- Installs on both smooth and corrugated jacketing
- No special tools, O-rings, transition gaskets, contoured flanges or "goof plates" required
- Reusable
- Patented design seals and protects against corrosion under the insulation (CUI), chemical and UV exposure of the elastomer sleeve
- Lanyard stops plug cap loss
- Available in 1.5, 2.5, 3.0 and 5.0 in. (38, 64, 76 and 127 mm) sizes with or without handle, lanyard and locking ring, as shown

Stroud Systems, Inc.
600 North Shepherd Drive, Suite 115
Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com

Material Specifications

The NDT Inspection Plug consists of an elastomer sleeve and a metal cap, with or without handle, lanyard and locking ring. The elastomer Sleeve is available in either EPDM (ethylene propylene) or silicone.

	EPDM	Silicone
Color	Black	Gray
ASTM Designation	D2000 2BA 510 A14 B13 C12 F17	D2000 2GE 506 A19 B37 F19
Temperature Range	-65° to +300° F -54° to +149° C	-65° to +400° F -54° to +204° C
Ozone Resistance	Outstanding	Excellent
Weathering Resistance	Outstanding	Excellent

The metal Cap is available in either 5052 aluminum or 304 stainless steel. The optional handle and locking ring would be of the same material. All lanyards are 304 stainless steel.

Also available are hole saws, arbors and TML Inspection Point Labels.

Design Specifications

NDT Plug Sizes Available	Recommended for Insulation Jacket OD
1.5 in. (38 mm)	Small Diameter Piping
2.5 in. (64 mm)	Minimum 6 in. (152 mm)
3.0 in. (76 mm)	Minimum 9 in. (229 mm)
5.0 in. (127 mm)	Vessels & Equipment

Inspection Access Procedure

- Locate and mark the insulation jacket where the test is required.
- Use either tin snips or a hole saw to penetrate the insulation.
- Remove the final layer of insulation in the safest and most convenient manner (using your hand or knife) to expose the substrate for electronic and visual inspection.
- After inspection, re-insert the insulation or replace with a high density material.
- Insert the Sleeve. (Caulk around the sleeve for cold applications is recommended.)
- Secure the Locking Ring and Lanyard (if applicable).
- Insert the Plug Cap to affect a seal.

Stroud Systems, Inc.
600 North Shepherd Drive, Suite 115
Houston, TX 77007-1324

713-861-3270

sales@stroudsystems.com